

Aluminium flexible duct pipe



Item	Colour	Ø pipe mm	Length mt
TFLA82	aluminium	82	10
TFLA102	aluminium	102	10
TFLA127	aluminium	127	10
TFLA152	aluminium	152	10
TFLA160	aluminium	160	10
TFLA180	aluminium	180	10

Description: Flexible and extendable duct

Material: Duct wall in aluminum laminate with reinforcement consisting of a high-carbon steel wire spiral embedded between two layers.

Features:

- Reaction to fire: EN 13823: 2020 / EN ISO 11925: 2020 / EN 13501-1: 2019 / B - s1, d0
- Bending radius: from 0.5 to 0.8 times the diameter
- Operating temperature: -30 / +130 °C
- Maximum operating pressure: 2500 Pa
- Maximum internal air velocity: 30 m/s



Aluminium flexible duct pipe



Item	Colour	ø pipe mm	Length mt
TFLA204	aluminium	204	10
TFLA229	aluminium	229	10
TFLA254	aluminium	254	10
TFLA305	aluminium	305	10
TFLA315	aluminium	315	10

Description: Flexible and extendable duct

Material: Duct wall in aluminum laminate with reinforcement consisting of a high-carbon steel wire spiral embedded between two layers.

Features:

- Reaction to fire: EN 13823: 2020 / EN ISO 11925: 2020 / EN 13501-1: 2019 / B - s1, d0
- Bending radius: from 0.5 to 0.8 times the diameter
- Operating temperature: -30 / +130 °C
- Maximum operating pressure: 2500 Pa
- Maximum internal air velocity: 30 m/s

